

ROUND FIBERGLASS FORMS FOR MORTAR JOINTS

STANDARD PREMIUM STRAIGHT WALL/ FLATWALL STRUCTURES

- For holes NOT intended for field installed rubber connectors.
- Both through holes and partial indentation knock out forms available
- Partial hole/ knockouts must be ordered with attachment so they can be held tight to jacket wall.
- Hole form diameters do not represent specific inside pipe diameter application.
- Super durable built at 5/16" laminate thickness with a concrete resistant glossy white polyester gelcoat.

Wall Thickness	6 Inch Wall	Wall Taper	8 Inch Wall	Wall Taper	12 Inch Wall	Wall Taper
Hole Form Face Dia. (Inner toward core)	Part No.	Degrees	Part No.	Degrees	Part No.	Degrees
4"	46	10	48	10		
5"	56	6				
6"	665	5	68	5		
6"	66	15				
8"	86	20	88	10		
10"	106	10	108	10		
12"	126	12	128	12		
14"	146	10	148	10		
15"	156	10	158	10	1512	10
16"	166	10	168	10		
18"	186	10	188	10	1812	10
20"	206	10	208	10	2012	10
21"	216	10				
22"	226	10	228	10	2212	10
23"	236	10				
24"	246	5 or 15	248	15	2412	5
25"	256	3				
26"	266	10	268	10	2612	5 or 10
27"	276	5	278	5		
28"	286	10	288	10	2812	10
30"	306	10	308	10	3012	5
32"	326	10	328	10	3212	10
34"	346	10	348	10	3412	10
36"	366	10	368	10	3612	10
38"	386	20	388	20	3812	10
40"	406	18	408	18		
41"	416	10	418	10		
42"	426	10	428	10	421210	10
44"	446	14	448	14		
46"	466	14	468	14		
48"	486	10	488	10		
52"	526	6	528	6		
55"	556	5	558	5		
58"	586	5	588	5		
60"	606	5	608	5		
62"	626	10	628	10		
65"	656	10	658	10		
70"	706	10	708	10		
72"	826	10	728	10		
78"	786	10	788	10		

* We can create a custom sized mold that is not currently listed in this table.

Revised: 6/12/2023