

LOW DRAFT/ MINIMUM TAPER

STANDARD PREMIUM HOLE FORMS

- 2° wall taper to accommodate the installation of flexible rubber manhole connector.
- Smooth surface concrete resistant polyester white gel coat for easier extraction.
- Diameter tolerances allow for use of either toggle or adjustable band type connectors.
- Super durable 3/8" overall fiberglass laminate thickness.
- Structural ribs in back cavity to reduce impact blowout of face on face diameters 20" and greater.

DIA.	6"	8"	48 x 5	48 x 8	60 x 6	72 x 7	84 x 8	84 x 8 3/4	96 x 9	96 x 9 3/4	120 x 11	120 x 11 3/4	144 x 13	144 x 13 3/4
7"	7L6	7L8	7L485		7L606	7L727								
8"	8L6	8L8	8L485		8L606	8L727	8L848	8L8483/4	8L969	8L9693/4	8L12011	8L120113/4	8L14413	8L144133/4
10"	10L6	10L8	10L485		10L606									
10.5"	10.5L6	10.5L8	10.5L485		10.5L606	10.5L727								
11"	11L6	11L8	11L485		11L606	11L727								
12"	12L6	12L8	12L485	12L488	12L606	12L727	12L848	12L8483/4	12L969	12L9693/4	12L12011	12L120113/4	12L14413	12L144133/4
13"					13L606	13L727								
14"			14L485											
16"	16L6	16L8	16L485		16L606	16L727								
18"	18L6	18L8	18L485		18L606	16L727								
20"	20L6	20L8	20L485		20L606	20L727								
22"	22L6	22L8	22L485		22L606	22L727								
24"	24L6	24L8	24L485		24L606	24L727								
26"	26L6	26L8	26L485		26L606	26L727								
28"	28L6	28L8	28L485		28L606	28L727								
30"	30L6	30L8	30L485		30L606	30L727								
32"	32L6	32L8	32L485		32L606	32L727								
34"	34L6	34L8	34L485		34L606	34L727								
36"	36L6	36L8												